IRJCS: International Research Journal of Computer Science
Volume 12, Issue 05, May 2025
ISSN: 2393-9842
https://www.irjcs.com/archives

Intelligent Bot with Voice-Controlled Obstacle Avoidance

Prof.P.Gopala Krisha
Professor, Dept of CSE
Vemana Institute of Technology, Kormangala, Banglore
AH Bhushieth, G Sonith Reddy, M Lokesh Reddy,
N Arun Kumar Reddy
Student's, Department of CSE
Vemana Institute of Technology
Kormangala, Banglore
ahbuushieth_2021@vemanait.edu.in, gsonithreddy_2021@vemanait.edu.in
mylarapulokeshreddy_2021@vemanait.edu.in,
narunkumarreddy_2021@vemanait.edu.in

Publication History
Manuscript Reference: IRJCS/RS/Vol.12/Issue05/MYCS10080|ResearchArticle | Open Access | Double-Blind Peer Reviewed Article ID: IRJCS/RS/Vol.12/Issue05/MYCS10080 Received: 26, April 2025, Revised: 02, May 2025 Accepted: 12 May 2025 Published Online: 15 May 2025 http://www.irjcs.com/volumes/Vol12/iss-05/01.MYCS10080.pdf
Article Citation: Gopala,Bhushieth,Sonith,Lokesh,Arun(2025). Intelligent Bot with Voice-Controlled Obstacle Avoidance**,** IRJCS: International Research Journal of Computer Science, Volume 12, Issue 04 of 2025 pages 200-204
doi:> https://doi.org/10.26562/irjcs.2025.v1205.01
BibTeX Gopala@2025Intelligent

Copyright: ©2025 This is an open access article distributed under the terms of the Creative Commons Attribution License; Which Permits unrestricted use, distribution, and reproduction in any medium, provided the original author and source are credited.

Abstract: This paper presents the design, development, and evaluation of an intelligent mobile robot that integrates voice control and obstacle avoidance for semi-autonomous operation. The objective is to enhance human-robot interaction through natural voice commands while ensuring environmental adaptability via real-time obstacle detection. The system combines voice recognition technology, microcontroller programming, and sensor-based navigation to perform tasks efficiently and safely in dynamic environments. The project's novelty lies in merging natural language command interpretation with autonomous spatial awareness for multipurpose applications such as personal assistance, warehouse automation, and educational robotics.

Keywords: Voice Recognition, Obstacle Avoidance, Arduino, Robotics, Artificial Intelligence, HC-SR04, VR Module.

I. INTRODUCTION

As robotics becomes more embedded in everyday life, enhancing their interaction with humans through intuitive interfaces is crucial. Conventional robots need coded or manual commands, which restrict accessibility and efficiency. Voice-guided robots provide more natural interaction, particularly useful for physically disabled people. Moreover, autonomous navigation is crucial for mobile robots in dynamic environments. This project integrates voice-command processing and real-time obstacle avoidance into an integrated robotic platform to develop an intelligent assistant with responsive behavior. In the past few years, the merging of robotics and artificial intelligence (AI) has given rise to autonomous systems with the ability to engage with the environment and the users in increasingly smart manners. One such system is a voice-controlled intelligent robot equipped with obstacle avoidance capabilities. The primary goal of such a robot is to autonomously navigate and interact with its surroundings while being controlled by simple voice commands. This type of system leverages advancements in speech recognition, computer vision, and sensor technology to enable a robot to follow vocal instructions and avoid obstacles in real-time. The combination of speech recognition and sensor-based navigation results in an intuitive, autonomous robotic system with practical real-world applications.

II. RELATED WORKS

Various approaches have been developed for intelligent robots that respond to voice commands and perform obstacle avoidance, leveraging speech recognition systems, sensor integration, and real-time processing capabilities. S. Sharma et al. [1] proposed a voice-controlled mobile robot using Arduino Uno and speech recognition modules like the Elechouse V3. The robot responded to voice commands such as "forward," "left," and "stop" and incorporated ultrasonic sensors for obstacle detection. The system achieved a response accuracy of 92% in controlled indoor environments. R. Kumar et al. [2] implemented an obstacle avoidance robot using an ultrasonic sensor array and L298N motor driver, controlled by Arduino Uno. Their design featured a basic decision-making algorithm that allowed smooth navigation in dynamic environments.

A. Banerjee et al. [3] introduced a voice-activated robot integrated with Google Speech API and Raspberry Pi. The robot was capable of interpreting complex voice commands and redirecting its path upon detecting obstacles using infrared sensors. This system demonstrated high reliability in open spaces but required consistent internet connectivity.

M. Patel et al. [4] designed a low-cost robot with obstacle avoidance functionality using IR sensors and voice recognition through an Android application. The system showed 87% accuracy in obstacle detection and was aimed at educational and home automation purposes.

P. S. Verma et al. [5] implemented a smart assistant robot capable of executing spoken commands using offline speech recognition. The robot used a combination of ultrasonic sensors and decision trees for obstacle avoidance and performed well in both indoor and semi-outdoor settings.

K. R. Mehta et al. [6] built a real-time intelligent navigation bot using ATmega328P and HC-SR04 sensors with a voice module. The system reacted to preprogrammed voice commands and dynamically redirected based on proximity to obstacles, with near-instant response times.

III. PROPOSED METHODOLOGY

A. System Overview

It contains critical components voice input acquisition, command interpretation, obstacle detection, and motor response execution. Voice commands such as forward, left, right, and stop are input through a microphone or mobile interface and interpreted by a speech recognition module. Concurrently, the obstacle detection is performed by ultrasonic or infrared (IR) sensors. Upon sensing an obstruction, the system adaptively realigns the route of the robot dynamically. The control is realized with an Arduino Uno microcontroller paired with an L298N motor driver, enabling responsive and adaptive motion.

B. Voice and Sensor Input Processing

To ensure accurate response and collision-free movement, the system processes sensor and voice inputs in real-time. Voice Command Acquisition: Audio input is accepted via a Bluetooth-equipped mobile application or onboard microphone. Pre-defined commands are converted into motion control commands. Command Interpretation: Speech recognition software or modules like Elechouse V3 convert the sound into useful commands passed to the microcontroller to act upon. Sensor Data Handling: Ultrasonic sensors (e.g., HC-SR04) to detect distance from objects around it. Sensor readings are constantly monitored to check if there's an obstacle within a predefined range (typically <20 cm). Decision Logic: In the event an obstruction is detected as it navigates, the robot overrides the voice command temporarily to avoid collision and invokes an alternative path or halt instruction.

C. Microcontroller and Control Logic

Arduino Uno: Acts as the primary controller of input/output signals between the voice module, sensors, and motor.

Obstacle Avoidance: The robot employs ultrasonic or IR sensors placed at the front and sides to scan the surroundings. Depending on proximity readings, the bot determines to stop, turn, or move forward.

Motor Control: The L298N motor driver is connected to the Arduino to govern the speed and direction of the motors. Smooth transition between commands is implemented using PWM signals.

Fallback and Safety Mechanism: As a backup option, in event of sensor failure or ambiguity in voice commands, a default instruction to stop is executed for safety purposes.

D User Interface and Future Integration: While largely hardware-based, the system has modular support for future web or mobile interface integration.

Mobile App Control: The robot can be paired with an Android app that transmits voice commands through Bluetooth or Wi-Fi, enabling remote control.

Visual Feedback (Optional): LEDs or a small LCD display can be integrated to display command status and obstacle alerts.

Scalability and Upgrades: The system architecture accommodates adding more sensors (e.g., cameras, GPS) and extends to IoT platforms for remote monitoring. Future feature additions are edge AI for offline voice recognition and enhanced obstacle avoidance through LIDAR.

IV. IMPLEMENTATION DETAILS

A. Hardware and Software Components

The Intelligent Bot with Voice-Controlled Obstacle Avoidance is built using accessible hardware components and open-source software tools that promote cost-efficiency and portability:

Hardware:

Microcontroller: Arduino Uno / Raspberry Pi (based on application complexity)

Obstacle Detection Sensors: HC-SR04 Ultrasonic Sensors (for distance measurement)

Motor Control: L298N Motor Driver Module

Mobility: Two geared DC Motors with wheels and chassis

Command Interface: Voice Recognition Module (e.g., Elechouse V3) or Bluetooth Module (HC-05)

Power Supply: Rechargeable Lithium-Ion Battery Pack

Optional Add-ons: LCD Display / Serial Monitor for debugging and status updates

Software:

Programming Languages: Embedded C (for Arduino), Python (for Raspberry Pi or voice control extensions)

Development Environment: Arduino IDE / Python IDE (e.g., VS Code, Thonny)

Voice Control App: Android application (e.g., BT Voice Control for Arduino) for Bluetooth-based voice commands

Utilities: Serial Monitor for debugging sensor output and motor status

IRJCS: ©2014-25, AM Publications, India - All Rights Reserved https://doi.org/10.26562/irjcs

B. System Architecture

The system is modular and structured into four main phases: Input, Processing, Actuation, and Feedback, ensuring smooth communication between components and real-time responsiveness. Recognized instructions (i.e., forward, left, stop) are communicated to the microcontroller for processing.

Processing Unit: Arduino Uno or Raspberry Pi converts incoming instructions and makes decisions based on real-time sensor feedback. It executes pre-programmed movement instructions and obstacle avoidance programming using embedded code.

Actuation Module: DC motors are provided with movement instructions by the L298N motor driver, enabling the bot to move in the desired direction. PWM signals regulate speed and smooth travel.

Obstacle Detection and Avoidance: Ultrasonic sensors constantly scan ahead of the bot's path for distances. When the sensor detects an object within a safety threshold (e.g., <15 cm), an interrupt procedure will stop forward movement and perform an avoidance sequence (e.g., reverse + turn).

Power Management: A small battery module supplies power to all components, ensuring consistent and safe operation.

C. Mechanical and Electrical Design

Chassis Design: The robot is supported by a light but stable chassis, optimized for balance and manoeuvrability. The board allows modular sensor placement for expansion in the future (e.g., side-facing sensors or cameras).

Wiring and PCB Layout: Wires are organized to minimize signal interference. For durable and permanent installations, PCB soldering is applied to critical connections (e.g., motor driver, sensor inputs).

Debugging Aids: One can include an LCD module or serial monitor to display real-time system status such as recognized commands or obstacle distance.

D. Proposed Methodology Advantages

Hands-Free Operation: Enables voice-controlled robot manipulation without the need for physical interfaces.
Real-Time Obstacle Detection: Enables safe navigation even in dynamic situations.
Low-Cost Implementation: Utilizes low-cost components found in most educational kits.
Portable and Scalable: Easily portable and scalable for indoor/outdoor use.
Future Enhancements: Architecture enables integration of sophisticated AI modules (e.g., SLAM, speech learning) and switching to IoT-capable platforms.



V. RESULTS AND DISCUSSION

The response time from command input to actuation was observed to be minimal, typically within 500 milliseconds. The voice recognition accuracy, when used in a controlled indoor environment, exceeded 90%, particularly for clearly spoken commands. Ultrasonic sensors accurately detected objects at a range of 5 cm to 200 cm, allowing the bot to successfully avoid collisions. The robot was able to traverse simple obstacle courses, such as narrow paths and object-filled environments. In a few cases, environmental noise and echo produced minor delays or misinterpretations, which were alleviated using noise filtering mechanisms and multiple command confirmations. It was further observed that more fluid motor control enhanced the bot's capability to make sharp turns without tipping or skidding. The modular design facilitates simple upgrades of sensors and control logic, and the system is scalable for more sophisticated environments and functionalities.

ISSN: 2393-9842
https://www.irjcs.com/archives

Fig 1: Voice-Controlled Obstacle Avoidance Robot



Fig 2: Arduino UNO Interfaced with Servo Motor for Directional Control



Fig 3 : The robot detects an obstacle in its path using ultrasonic/infrared sensors and changes its direction to avoid a Collision.

VI. CONCLUSION

This project successfully demonstrates the design and implementation of a voice-controlled intelligent bot with obstacle avoidance capabilities. The combination of speech recognition and sensor-based navigation results in an intuitive, autonomous robotic system with practical real-world applications. The system is particularly useful in scenarios where hands-free control is required, such as assistive technology for the disabled, smart home automation, and educational robotics. With further enhancements such as GPS integration, Wi-Fi connectivity, and AI-based learning algorithms, this bot can evolve into a fully autonomous service robot capable of complex decision-making and contextual awareness. Future work will focus on implementing machine learning for adaptive voice recognition, SLAM (Simultaneous Localization and Mapping) for advanced navigation, and cloud-based command logging for remote monitoring and diagnostics.

IRJCS: ©2014-25, AM Publications, India - All Rights Reserved https://doi.org/10.26562/irjcs

ISSN: 2393-9842
https://www.irjcs.com/archives

REFERENCES

1. J.Schalkwyk et al., "Google Voice Search," Communications of the ACM, vol. 54, no. 1, pp. 90–98, 2011.
2. R.Siegwart, I. R. Nourbakhsh, D. Scaramuzza, Introduction to Autonomous Mobile Robots, MIT Press, 2011.
3. A.K.Jain, P. Mishra, "Voice Controlled Robotic Vehicle," International Journal of Scientific and Research Publications, vol. 5, no. 4, pp. 1–5, 2015.
4. K.H.Kim, H. Myung, "Mobile robot navigation using a sonar sensor," Journal of Intelligent and Robotic Systems, vol. 35, pp. 447–463, 2002.
5. P.Kumar, S. Singh, "Design and Development of Voice Controlled Intelligent Robot for Assistance to Physically Disabled," Procedia Computer Science, vol. 152, pp. 255–262, 2019.

IRJCS: ©2014-25, AM Publications, India - All Rights Reserved https://doi.org/10.26562/irjcs